

**KHE 2444 (606154000) Combination Hammer**  
(220-240 V / 50 Hz); Plastic Carry Case

Order no. 606154000  
EAN 4007430203748



Product may differ from Image



- Combination hammer with 3 functions: hammer drilling, drilling and chiselling
- Vario (V)-Electronics for working at customised speeds to suit various application materials
- Metabo S-automatic safety clutch: mechanical decoupling of the drive for safe working should the drill stop unexpectedly
- Lockable switch for comfortable working in continuous operation

## Technical data

### Characteristics

Max. single blow energy (EPTA)	2.3 J
Maximum impact rate	5400 bpm
Rated input power	800 W
Drill-Ø concrete with hammer drills	24 mm / 1 "
Drill-Ø masonry with core bits	68 mm / 2 5/8 "
Drill Ø steel	13 mm / 1/2 "
Drill-Ø soft wood	30 mm / 1 3/16 "
No-load speed	0 - 1230 rpm
Revolutions at rated load	880 rpm
Bit retainer	SDS-plus
Collar diameter	43 mm / 1 11/16 "
Weight (without power cable)	2.4 kg / 5.3 lbs
Cable length	4 m / 13 ft

### Vibration

Hammer drilling concrete	13.7 m/s <sup>2</sup>
Uncertainty of measurement K	1.5 m/s <sup>2</sup>
Chiseling	15 m/s <sup>2</sup>
Uncertainty of measurement K	1.5 m/s <sup>2</sup>

### Noise emission

Sound pressure level	87 dB(A)
Sound power level (LWA)	98 dB(A)
Uncertainty of measurement K	3 dB(A)

## Scope of delivery

Hammer chuck for tools with SDS-plus shank end  
 Plastic carry case  
 Side handle  
 Drilling depth guide