

**WEV 15-125 Quick Inox (600572000) Angle Grinder**  
(220-240 V / 50 - 60 Hz); Cardboard box

Order no. 600572000  
EAN 4007430245373



Product may differ from image



- Perfect processing of stainless steel: robust, powerful angle grinder with high gear reduction and adjustable reduced speed for cool finish
- Longer service life, more power: the Metabo Marathon-motor with patented dust protection, up to 20% more overload capacity and 50% more torque
- Vario Tacho Constamatic (VTC) Full-wave Electronics with Thumbwheel: for working at customised speeds to suit the application material and speeds that remain almost constant, even under load
- Tool free, fast disc change at the touch of a button with the Metabo M-Quick-System
- Tool-free adjustable guard; twist-proof
- Low-vibration side handle Metabo VibraTech (MVT)
- Metabo S-automatic mechanical safety clutch: minimises kick-back to the lowest level when the disc jams unexpectedly - for maximum user safety and swift progress
- Electronic overload protection, soft start and restart protection
- Gear housing can be unscrewed, rotated in 90° steps and remounted for left-handed operation or cutting
- Auto-stop carbon brushes to protect the motor

## Technical data

### Characteristics

Grinding wheel Ø	125 mm / 5 "
Rated input power	1550 W
Output power	940 W
No-load speed	2000 - 7600 rpm
Revolutions at rated load	7600 rpm
Torque	5 Nm / 44 in-lbs
Spindle thread	M 14
Weight (without power cable)	2.5 kg / 5.5 lbs
Cable length	4 m / 13 ft

### Vibration

Surface grinding	4.7 m/s <sup>2</sup>
Uncertainty of measurement K	1.5 m/s <sup>2</sup>
Polishing	2.5 m/s <sup>2</sup>
Uncertainty of measurement K	1.5 m/s <sup>2</sup>
Grinding with sandpaper	2.5 m/s <sup>2</sup>
Uncertainty of measurement K	1.5 m/s <sup>2</sup>

### Noise emission

Sound pressure level	93 dB(A)
Sound power level (LwA)	104 dB(A)
Uncertainty of measurement K	3 dB(A)

## Scope of delivery

Guard  
Metabo VibraTech (MVT) side handle  
Inner support flange  
M-Quick flange nut