

GE 950 G Plus (600618000) Die Grinder (220-240 V / 50 - 60 Hz); Cardboard box

Order no. 600618000 EAN 4007430212412



Product may differ from Image

- High torque and compact design thanks to robust planetary gear
- Spindle lock for simple change of tools
- Aluminium die-cast bearing flange for long service life of the machine
- Vario-Constamatic (VC)- Electronics for work with materials requiring customised speeds, which remain almost constant under load
- Thumbwheel for Speed Preselection
- Electronic safety shutdown of the motor for safe working in case the tool stops unexpectedly
- Restart protection: prevents unintentional start-up after power supply interruption
- Electronic overload protection for long service life
- Precise collar for stationary use
- Removable protective rubber cap for comfortable and safe working
- Slim design for ideal handling
- Precision collet for precise concentricity
- Metabo Marathon motor with patented dust protection for long service life
- The specialist: handy grinder with especially high torque; ideal for grinding inner and outer surfaces in combination with flap wheels (see Accessories)



Technical data

Characteristics

| No-load speed | 2500 - 8700 rpm |
|----------------------------------|----------------------|
| Rated input power | 950 W |
| Output power | 510 W |
| Revolutions at rated load | 7200 rpm |
| Collar diameter | 43 mm / 1 11/16 " |
| Collet chuck bore | 6 mm / 0.2362 " |
| Weight (without power cable) | 1.7 kg / 3.7 lbs |
| Cable length | 4 m / 13 ft |
| Vibration | |
| Surface grinding (up to Ø 25 mm) | 2.5 m/s ² |
| Surface grinding (up to Ø 50 mm) | 2.5 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |
| Noise emission | |
| Sound pressure level | 87 dB(A) |
| Sound power level (LwA) | 98 dB(A) |
| Uncertainty of measurement K | 3 dB(A) |
| | |

Scope of delivery

Collet 6 mm 1 Open-jawed spanner Protective rubber cap

Side handle