

**RS 17-125 (603822710) Renovation Grinder**  
(220-240 V / 50 - 60 Hz); Plastic Carry Case; with Diamond Cup Wheel Concrete "professional"

Order no. 603822710  
EAN 4007430246431



Product may differ from Image



- For effective spot sanding and removal of concrete, screed and coatings with diamond cup wheels
- High torque and overload capacity for demanding applications in continuous use
- Working close to edges thanks to integrated folding segment
- Optimum extraction results: spring-mounted brush rim at the protective cover that adapts to any surface and segment height
- Front handle for safe and uniform guidance when polishing, adjustable without tools
- Metabo Marathon motor with patented dust protection for long service life
- Electronic soft start for smooth start-up
- Restart protection: prevents unintentional start-up after power supply interruption
- Overload protection: protects the motor from overheating
- Metabo safety switch prevents unintentional start
- Auto-stop carbon brushes to protect the motor
- Aluminium flange for long service life when using heavy accessories, e.g. diamond cup wheels

## Technical data

### Characteristics

Grinding wheel Ø	125 mm / 5 "
Torque	6 Nm / 53 in-lbs
No-load speed	8500 rpm
Rated input power	1700 W
Output power	950 W
Revolutions at rated load	5700 rpm
Spindle thread	M 14
Weight (without power cable)	4.8 kg / 10.6 lbs
Cable length	4 m / 13 ft

### Vibration

Surface grinding	3.8 m/s <sup>2</sup>
Uncertainty of measurement K	1.5 m/s <sup>2</sup>

### Noise emission

Sound pressure level	93 dB(A)
Sound power level (LWA)	104 dB(A)
Uncertainty of measurement K	3 dB(A)

## Scope of delivery

Bow-type handle  
 Plastic carry case  
 Diamond cup wheel concrete "professional"  
 Flat-pin spanner  
 Inner support flange  
 Nut with two holes