

**SXE 450 TurboTec (600129000) Random Orbital Sander**  
(220-240 V / 50 Hz); Cardboard box

Order no. 600129000  
EAN 4007430164339



Product may differ from Image

- Patented adjustable "Duo" oscillating circuit setting: Can be set depending on the application for fine sanding or high stock removal
- Variospeed (V) Electronics for working at customised speeds to suit various application materials
- Thumbwheel for speed preselection
- Turbo boost: allows additional power reserves to be employed for maximum removal
- Power Control System: No scratches when placing the machine directly onto the material at speed
- Grip area with non-slip soft-grip surface
- Removable side handle
- Dust-proof ball bearings for long service life of the machine
- Sturdy aluminium die cast bearing housing
- Easy to empty textile dust bag for working without extraction facilities
- Extraction possibility by means of connecting an all-purpose vacuum cleaner
- Multi-hole sanding pad for effective extraction and a longer service life of the sanding medium

## Technical data

### Characteristics

|                              |                  |
|------------------------------|------------------|
| Diameter of backing pad      | 150 mm / 6 "     |
| No-load speed                | 4200 - 11000 rpm |
| Rated input power            | 350 W            |
| Output power                 | 180 W            |
| Revolutions at rated load    | 8500 rpm         |
| Orbit diameter               | 2.8 mm / 1/8 "   |
| Weight (without power cable) | 2.2 kg / 5.3 lbs |
| Cable length                 | 4 m / 13 ft      |

### Vibration

|                              |                      |
|------------------------------|----------------------|
| Surface grinding             | 7 m/s <sup>2</sup>   |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup> |

### Noise emission

|                              |          |
|------------------------------|----------|
| Sound pressure level         | 82 dB(A) |
| Sound power level (LwA)      | 93 dB(A) |
| Uncertainty of measurement K | 3 dB(A)  |

## Scope of delivery

Sanding pad "multi-hole" with hook and loop  
Textile dust bags  
Hexagonal wrench  
removable side handle