

Basic 250-24 W (601533000) Compressor Basic
(220-240 V / 50 Hz); Cardboard box

Order no. 601533000
EAN 4007430244420



Product may differ from Image



- Powerful, robust compressor for simple, commercial use
- Oil-lubricated Piston Condenser
- For single phase alternating current
- Operating pressure can be regulated according to application by means of a pressure reducer and manometer
- Convenient pressure switch for good cold starting, complete with relief valve
- Overload protection: protects the motor from overheating
- Rubberised, stable wheels for mobile use
- Additional manometer for displaying the tank pressure
- Rubber-coated handle for comfortable handling
- 10 year tank warranty against rust

Technical data**Characteristics**

| | |
|--|---|
| Suction rate | 200 l/min / 53 gal/h |
| Filling capacity | 110 l/min / 3.9 cfm |
| Effective delivery volume (at 80% max. pressure) | 95 l/min / 3.4 cfm |
| Maximum pressure | 8 bar / 116 psi |
| Rated input power | 1.5 kW / 2 HP |
| Maximum speed | 2850 rpm |
| Tank capacity | 24 l / 6.3 gal |
| Sound pressure level (LpA) | 81 dB(A) |
| Sound power level (LwA) | 97 dB(A) |
| Dimensions | 620 x 340 x 580 mm / 24 13/32 x 13 3/8 x 22 27/32 " |
| Weight | 27 kg / 59.5 lbs |
| Cable length | 1.5 m / 5 ft |

Noise emission

| | |
|-------------------------|----------|
| Sound pressure level | 81 dB(A) |
| Sound power level (LwA) | 97 dB(A) |

Scope of delivery

Universal quick-action coupling
Pull handle with rubber-grip